

STU-1K

"STU-1K" : Capteurs traction/compression



Capteurs en traction/compression, idéal pour le pesage en traction des charges suspendues et pour le contrôle et la limitation de la surcharge, ou pour une utilisation en compression pour la réalisation de systèmes de pesage avec plusieurs capteurs.

PORTEE (kg) : 2000, 5000, 8000, 10000.

OIML R60. Classe de précision **C3**.

Acier **INOX**. Degré de protection **IP68**.

La solution idéale pour
les applications industrielles
évoluées

CARACTERISTIQUES PRINCIPALES

- CLASSE DE PRECISION C3
- CORPS EN ACIER INOX
- DEGRE DE PROTECTION IP68
- PORTEE MAX DE 2000 kg A 10000 kg
- CABLE DE CONNEXION BLINDE DE 3 MÈTRES

CARACTERISTIQUES TECHNIQUES

- nLC: 3000
- Y: 12000 (compression, $Y=E_{max}/V_{min}$)
- Y: 9500 (tension, $Y=E_{max}/V_{min}$)
- Cn: 2,4 mV/V
- Input: 1000 +/- 20 Ohms
- Output: 1000 +/- 5 Ohms
- Alimentation 1...10 Vdc
- Surcharge 120% Emax
- Câble blindé 6 pôles, longueur 3 m, diamètre 5 mm.

CERTIFICATIONS PRINCIPALES

- OIML R60
- Australian legal for trade certificate of approval (NMI S840)

DETAIL 1



Connexions capteur	
<i>Colour</i>	<i>Fonction</i>
METAL	BLINDAGE
JAUNE	SIGNAL +
GRIS	SENSE +
MARRON	ALIMENTATION +
BLANC	SIGNAL -
ROSE	SENSE -
VERT	ALIMENTATION -

VERSIONS

Versions disponibles

Codice	Max (kg)
STU2000-1KD 	2000
STU5000-1KD 	5000
STU8000-1KD 	8000
STU10000-1KD 	10000



www.diniargeo.com

“YOUR WORLDWIDE PARTNER FOR WEIGHING”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE