

SC2D

SCANNER DE CODES BARRES DE LA SÉRIE "SC2D"



Lecteur de codes barres avec pistolet à câble pour l'indicateur de poids de la série 3590 TOUCH SCREEN. Fonctionnement manuel par bouton poussoir ou automatique lorsqu'il est installé sur la base.

Caractéristiques :

- Lumière LED pour l'identification de la zone de balayage
- Rétroaction avec un signal acoustique
- Base de support incluse pour une utilisation en mode automatique
- OPTIQUE : Capteur de surface CMOS
- DIMENSIONS en mm (lxlxh) : 105 x 153 x 60 mm
- POIDS : 115 g
- ALIMENTATION : 5 Vdc de l'indicateur de poids
- LONGUEUR DU CÂBLE : 160 cm
- PROTECTION : IP42
- ENVIRONNEMENT D'UTILISATION : Température 5 à 50°C, Humidité max. 90% sans condensation

Codes-barres compatibles :

- Codes barres (1D) : UPC-A, UPC-E, UPC-E1, UPC-A Add-on , UPC-E Add-on, EAN-13, EAN-8, EAN-13 Add-on/EAN- 8 Add-on, JAN-8, JAN-13, Code 39, NW-7(Codabar), Industrial 2 of 5, Interleaved 2 of 5, Code 93, Code 128, GS1-128, MSI/Plessey, Code 11, OCR-B, GS1 DataBar, GS1 DataBar Limited ,GS1 DataBar Expanded, Composite GS1 DataBar, Composite GS1-128, Composite EAN, Composite UPC , TELEPEN
- Codes barres (2D) : PDF417, MicroPDF417, Codablock F, QR Code, Micro QR Code, DataMatrix (ECC 200), MaxiCode, Aztec Code, Chinese Sensible Code

DETAIL 1

DETAIL 2



DETAIL 3





“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 921784



SALES AND TECHNICAL ASSISTANCE SERVICE